

Product information



Absorption refrigerators



Noiseless, durable, ready for use anywhere

Tailor-made fridges for all types of vehicles

behind Dometic's absorption refrigerators. For are ease of use and the freedom they afford decades they have been the first choice for camping and caravanning enthusiasts. With a motorhome manufacturers as original fitting in choice of power options - battery, mains current or their vehicles. For good reason: thanks to a gas - and the widest possible selection of models, design that avoids the use of moving parts they anything and everything is possible with a Dometic are completely silent, highly resistant to wear absorption refrigerator.

A long history of unparalleled success lies and tear, and easy to maintain. Other advantages

The fridges of the future

They are here - the motorhome fridges of tomorrow! The new 8-series from Dometic combines contemporary product design with maximum efficiency. The removable freezer compartment is the first of its kind in the world and the subject of an exclusive patent. Large décor panels lend the refrigerators a unique furniture character. Available in various design options to suit specific demands. Capacities from 80 to 189 litres, with or without wheel arch cut-out.

Dometic 8-Series



RM 8505

Proven best-sellers with separate freezer compartment Pages 74 - 77

Spacious refrigeration compartment, large freezer compartment, each with a door of its own - these are the characteristic features of the successful Dometic 7-series. Available in capacities from 142 to 175 litres.

Dometic 7-Series



RM 7655

The classic models

The compact refrigerators of the famous 4-series have been installed in millions of caravans and motorhomes around the world! Their optimised exterior dimensions conceal a surprisingly spacious interior. Available in capacities from 40 to 97 litres.

Dometic 4-Series



RM 4181 M

Pages 64 - 73





RMS 8500



RML 8551



RM 7855

Pages 78 - 83





RM 4211 LM



RM 4401 L

Dometic 8-Series



The 8-series: the fridges of the future

Easy to use, stylish and ultra-efficient: the Dometic 8-series sets new standards for absorption refrigerators. Innovative designs and colourful accents transform the high-quality appliances into stylish design pieces. On the outside, décor panels help them blend in with the furniture while the inside is illuminated with energy-efficient LED lights that radiate a pleasantly cool blue light. A host of user-friendly features add the finishing touch.

Product highlights at a glance



1. Removable freezer compartment patented worldwide innovation Thanks to an innovative clip system the freezer compartment can be removed quickly and easily to increase refrigerator capacity if required and reduce energy consumption. A world first that is exclusive to the 8-series.



2. Flexible arrangement of shelves The improvements are clear to see. Easy-to-move shelves that can be positioned as needed. Just like at home ...

3. Innovative door system

Practical and convenient for daily use: the new locking system with fingertip opening. All models with AES system are equipped with an acoustic alarm that warns if the door is accidentally left ajar. 8-series refrigerators can be supplied with door hinges on the left or right as required.





acoustic alarms [AES models].

5. Modular freshness system

The vegetable compartment can be partitioned. Moreover, it can be removed and cleaned in the dishwasher, just like the ergonomically designed door shelves with leakage protection.

4. New control panel design

Future-orientated design also distinguishes the control panel, which is integrated perfectly into the refrigerator cabinet. For extra comfort and convenience, the refrigerators feature a user-friendly LED display with intuitive menu as well as visual alarm [MES models] or, respectively, visual and

Dometic 8-Series

The product name code for the 8-series

Every fridge in this new series has a "name" that consists of a letter code followed by a four-digit number. These indicate the finish and features of that particular appliance.

The letter code RM stands for a standard model, RMS means you have a wheel-arch model, RML denotes a large-capacity fridge.

An initial 8 in the four-digit combination indicates that the refrigerator is part of the 8-series. If the second digit is a 4 then the fridge is 486 mm wide while a 5 indicates a width of 525 mm. The third digit refers to the depth of the unit: a 0 stands for 569 mm standard depth, a 5 for 624 mm comfort depth.

The last digit informs you about the type of ignition used: 5 stands for AES, 1 for MES and 0 for battery-powered ignition.

Three ignition systems for various demands



The **AES system** [Automatic Energy Selector] automatically selects the best energy source to guarantee efficient refrigeration performance at all times. Alternatively, you can choose the type of energy manually. Thermostatic control for all energy sources. All AES refrigerators have a solar input socket S+ for operation with 12-volt solar power.

RMS 8505

Ignition system: AES

Standard depth: 569 mm

Width: 525 mm

Series: 8

Model version:


wheel arch cut-out



The **MES system** [Manual Energy Selector] features an electronic reigniter, which registers a dying flame and reignites it. Simply turn the controls to select the energy source manually. Thermostatic control for all energy sources.



Battery ignition means the gas is ignited by pressing a button. As soon as the flame goes out the gas supply stops. Thermostatic control for 230-volt and gas operation.



Product

Dometic RM 8500, door hinge left Dometic RM 8500, door hinge right Dometic RM 8501, door hinge left Dometic RM 8501, door hinge right Dometic RM 8505, door hinge left Dometic RM 8505, door hinge right



Gross capacity



Energy supply	
Input rating	230 volts 12 volts Gas
Consumption	230 volts/12 volts Gas
Cooling capacit	ty

RM 8501

Insulation System Material Colour Dimensions [WxHxD] Weight Quality features

Test marks

Absorption refrigerators


4.28 without freezer compartment 106 litres with freezer compartment 100 litres 9 litres incl. freezer compartment 230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mbar / category I3 B/P Refrigerator +7°C 135 watts freezer compartme 130 watts up to -12°C 18.3 g/h 2.0 to 2.2 kWh/24 h 250 to 270 g/24 h Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C [equivalent to climate class SN] 12/230 volts Pentane-blown foam [CFC-/HFC-free] Absorption cooling Cabinet, door and panel: plastic Cabinet: black-grey, door: silver-grey 525 x 821 x 569 mm Gas with freezer compartment 27.8 ka Patented removable freezer compartment. fingertip door opening, interior light, door with Patented. magnetic seal, replaceable door seals, door easy-to-remove locking with vent option, user-friendly control freezer compartment panel, flexible arrangement of shelves, ergonomic door shelves with leakage protection **RM 8500**: Gas operation with battery-powered Replaceable igniter, thermostatic control for 230-volt door seals and gas operation RM 8501: Manual Energy Selector [MES] with RM 8500: electronic gas ignition, thermostatic control for all Gas operation with operating modes battery-powered RM 8505: Automatic Energy Selector [AES] with ignition electronic gas ignition, thermostatic control for all operating modes Certified to European Gas Appliance Directive RM 8501: 90/396/EEC, e-approved to 2006/28/EC Manual Energy Selector [Automotive EMC Directive] [MES] with electronic gas ignition

RM 8505: Automatic Energy Selector [AES] with electronic gas ignition

Model

RM 8500, door hinge left RM 8500, door hinge right RM 8501, door hinge left RM 8501, door hinge right RM 8505, door hinge left RM 8505, door hinge right

series absorption refrigera gle-door models, 525 mr					
12 - 20	Gross capacity		without freezer compartment with freezer compartment incl. freezer compartment	96 litres 90 litres 9 litres	1000 M
	Energy supply		230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mba	r / category leas	325
	Input rating	230 volts 12 volts Gas	125 watts 120 watts 18.3 g/h	S S B/F	Refrigerator +7°C freezer compartment up to -12°C
All Contracts	Consumption	230 volts/12 volts Gas	2.0 to 2.2 kWh/24 h 250 to 270 g/24 h		A
1	Cooling capaci	ty	Refrigerator +7°C, freezer compar at ambient temperatures up to 3 [equivalent to climate class SN]	2°C	
	Insulation		Pentane-blown foam [CFC-/HFC		12/230 volts
	System		Absorption cooling		
IS 8500	Material		Cabinet, door and panel: plastic		
10 0000	Colour		Cabinet: black-grey, door: silver-	-grey	\mathbf{O}
	Dimensions [W	xHxD]	525 x 821 x 569 mm		
	Weight		with freezer compartment	25.5 kg	Gas
	-		Patented removable freezer com fingertip door opening, interior lig magnetic seal, replaceable door locking with vent option, user-fri panel, flexible arrangement of sh door shelves with leakage protect	ght, door with seals, door endly control nelves, ergonomic	Patented, easy-to-remove freezer compartment
			RMS 8500: Gas operation with the igniter, thermostatic control for 2 gas operation		Replaceable door seals
			RMS 8501 : Manual Energy Select with electronic gas ignition, there control for all operating modes		RMS 8500: Gas operation with battery-powered
			RMS 8505: Automatic Energy Se with electronic gas ignition, then control for all operating modes		ignition
	Test marks		Certified to European Gas Applia 90/396/EEC, e-approved to 2000 [Automotive EMC Directive]		RMS 8501: Manual Energy Selector [MES] with electronic gas ignition
					RMS 8505: Automatic Energy Selector [AES] with electronic gas ignition
523 ★ 101 981 400 +70					



Dometic RMS 8500, door hinge left Dometic RMS 8500, door hinge right Dometic RMS 8501, door hinge left Dometic RMS 8501, door hinge right Dometic RMS 8505, door hinge left Dometic RMS 8505, door hinge right

RMS 8500, door hinge left RMS 8500, door hinge right RMS 8501, door hinge left RMS 8501, door hinge right RMS 8505, door hinge left RMS 8505, door hinge right



523

Dometic RM 8551, door hinge left Dometic RM 8551, door hinge right Dometic RM 8555, door hinge left Dometic RM 8555, door hinge right

455

Absorption refrigerators

Dometic RM 8551 -	with Manual E	nergy Selector [I	MES]		4.28
Dometic RM 8555 -	with Automatio	c Energy Selecto	r [AES]		
8-series absorption refriger	rators for 12 v	olts, 230 volts an	d gas		
Single-door models, 525 m	m wide				
	Gross capacity	1	without freezer compartment with freezer compartment	122 litres 115 litres	(Stars
			incl. freezer compartment	12 litres	3882
	Energy supply		230 volts AC / 50 Hz 12 volts DC		***
			Liquefied petroleum gas 30 mba	ar / category I _{3 B/P}	Refrigerator +7°C
	Input rating	230 volts 12 volts Gas	135 watts 130 watts 18.3 g/h		freezer compartment up to -12°C
A COLUMN A COLUMN	Consumption	230 volts/12 volts Gas	2.1 to 2.3 kWh/24 h 250 to 270 g/24 h		(ARD)
Sector Course	Cooling capacity		Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C [equivalent to climate class SN]		12/230 volts
	Insulation		Pentane-blown foam [CFC-/HF	C-free]	
J	System		Absorption cooling		
RM 8551	Material		Cabinet, door and panel: plastic	;	
	Colour		Cabinet: black-grey, door: silver-grey		
	Dimensions [W	/xHxD]	525 x 821 x 624 mm		Gas
	Weight		with freezer compartment	29.0 kg	uas
	Quality feature	s	Patented removable freezer con fingertip door opening, interior li magnetic seal, replaceable door locking with vent option, user-fr panel, flexible arrangement of si door shelves with leakage prote	ight, door with seals, door iendly control helves, ergonomic	Patented, easy-to-remove freezer compartment
			control for all operating modes		Replaceable door seals
			RM 8551 : Manual Energy Select with electronic gas ignition	tor [MES]	
			RM 8555 : Automatic Energy Se with electronic gas ignition	lector [AES]	RM 8551: Manual Energy Selector [MES] with electronic
	Test marks		Certified to European Gas Appli 90/396/EEC, e-approved to 200 [Automotive EMC Directive]		gas ignition

RMS 8555: Automatic Energy Selector [AES] with electronic gas ignition


leboM

RM 8551, door hinge left RM 8551, door hinge right RM 8555, door hinge left RM 8555, door hinge right


Dometic 8-Series

door models, 486 mm	Gross capacity	/	without freezer compartment with freezer compartment	95 litres 90 litres	-
0 00			incl. freezer compartment	8 litres	2005
	Energy supply		230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mba	ar / category lass	Refrigerator +7°C
	Input rating	230 volts 12 volts Gas	125 watts 120 watts 18.3 g/h	3 B/F	freezer compartment up to -12°C
	Consumption	230 volts/12 volts Gas	2.0 to 2.2 kWh/24 h 250 to 270 g/24 h		Æ.
	Cooling capaci	ity	Refrigerator +7°C, freezer compared at ambient temperatures up to 3	2°C	W
	Inculation		[equivalent to climate class SN]		12/230 volts
	Insulation System		Pentane-blown foam [CFC-/HF0 Absorption cooling	o-nee]	
	Material		Cabinet, door and panel: plastic		
100	Colour		Cabinet: black-grey, door: silver-		\odot
	Dimensions [W	/xHxD1	486 x 821 x 569 mm		
	Weight		with freezer compartment RM 8400: 27.5 kg, RM 8401: 27.5 kg		Gas
	Quality features		Patented removable freezer com fingertip door opening, interior li magnetic seal, replaceable door locking with vent option, user-fri panel, flexible arrangement of sh	ght, door with seals, door endly control nelves, ergonomic	Patented, easy-to-remove freezer compartment
			door shelves with leakage protect RM 8400: Gas operation with ba ignition, thermostatic control for	attery-powered	Replaceable door seals
			and gas operation RM 8401: Manual Energy Select with electronic gas ignition, then control for all operating modes		RM 8400: Manual Energy Selector [MES] with electronic gas ignition
	Test marks		Certified to European Gas Applia 90/396/EEC, e-approved to 200 [Automotive EMC Directive]		RM 8401: Automatic Energy Selector [AES] with
					electronic gas ignition

Dometic RMS 8400 - with battery-powered ignition Dometic RMS 8401 - with Manual Energy Selector [MES] 8-series absorption refrigerators for 12 volts, 230 volts and gas Single-door models, 486 mm wide, wheel-arch cut-out Gross capacity without freezer compartment 85 litres with freezer compartment 80 litres incl. freezer compartment 8 litres **Energy supply** 230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mbar / category I3 B/P Input rating 230 volts 125 watts 12 volts 120 watts Gas 18.3 g/h 230 volts/12 volts 2.0 to 2.2 kWh/24 h Consumption Gas 250 to 270 g/24 h **Cooling capacity** Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C [equivalent to climate class SN] Insulation Pentane-blown foam [CFC-/HFC-free] Absorption cooling System Material Cabinet, door and panel: plastic RMS 8401 Colour Cabinet: black-grey, door: silver-grey Dimensions [WxHxD] 525 x 821 x 569 mm with freezer compartment Weight RMS 8400: 25.0 kg, RMS 8401: 25.0 kg Quality features Patented removable freezer compartment, fingertip door opening, interior light, door with magnetic seal, replaceable door seals, door locking with vent option, user-friendly control panel, flexible arrangement of shelves, ergonomic door shelves with leakage protection RMS 8400: Gas operation with battery-powered ignition, thermostatic control for 230-volt and gas operation RMS 8401: Manual Energy Selector [MES] with electronic gas ignition, thermostatic control for all operating modes Certified to European Gas Appliance Directive Test marks 90/396/EEC, e-approved to 2006/28/EC [Automotive EMC Directive]



Dometic RMS 8400, door hinge left Dometic RMS 8400, door hinge right Dometic RMS 8401, door hinge left Dometic RMS 8401, door hinge right





Dometic RM 8400, door hinge left Dometic RM 8400, door hinge right Dometic RM 8401, door hinge left Dometic RM 8401, door hinge right

Product

RM 8400, door hinge left RM 8400, door hinge right

Model

RM 8401, door hinge left RM 8401, door hinge right Product

Absorption refrigerators



4.28

Refrigerator +7°C freezer compartmen up to -12°C





Patented. easy-to-remove freezer compartment

Replaceable door seals

RMS 8400: Manual Energy Selector [MES] with electronic gas ignition

RMS 8401: Automatic Energy Selector [AES] with electronic gas ignition

Model

RMS 8400, door hinge left RMS 8400, door hinge right RMS 8401, door hinge left RMS 8401, door hinge right




Dometic RML: a giant of a fridge

Experience the biggest absorption refrigerator currently Large refrigerator capacity of 190 litres available anywhere! This refrigerator truly takes mobile refrigeration to a new level. A simple pull is all that is needed to remove the freezer compartment and turn the refrigerator into a cooling giant with a capacity of 189 litres. Perfect for leisure enthusiasts and their need for well-stocked supplies. When required the generously dimensioned freezer compartment offers 33 litres of space for frozen food. There is easily enough room for a family pizza and other jumbo-sized packs.

Of course the large-capacity refrigerator offers all of the usual advantages of the 8-series such as the new door catch, flexible arrangement of shelves, energy-efficient LED illumination and the cool blue interior design.

- [when 33-litre freezer compartment is removed]
- Single-door model, 525 mm wide
- Available with AES or MES system
- User-friendly control panel with LED display and integrated alarm function
- Three shelves can be arranged as required
- Three ergonomically shaped door shelves with leakage protection
- Vegetable bin with partition

Dometic RML 8551	- with Manual	Energy Selector	[MES]		4.28	
Dometic RML 8555 8-series absorption refrigu Single-door model, 525 m	erators for 12 vo	0,				
	Gross capacity		without freezer compartment with freezer compartment incl. freezer compartment	189 litres 179 litres 33 litres	-	
	Energy supply		230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mbs	ar / category I _{3 B/P}	Refrigerator +7°C	
	Input rating	230 volts 12 volts Gas	190 watts 170 watts 22.5 g/h		freezer compartment up to -12°C	
	Consumption	230 volts/12 volts Gas	3.0 to 3.2 kWh/24 h 360 to 380 g/24 h		(ATTA)	
	Cooling capacity		Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C [equivalent to climate class SN]		12/230 volts	
	Insulation		Pentane-blown foam [CFC-/HF	C-free]	12,200 1010	
	System		Absorption cooling			
	Material		Cabinet: coated sheet steel Door and panel: plastic		6	
RML 8555	Colour		Cabinet: black-grey, door: silver	r-grey		
	Dimensions [W	/xHxD]	525 x 1245 x 626 mm		Gas	
	Weight		with freezer compartment	44.5 kg		
	Quality features		Patented removable freezer cor fingertip door opening, interior I magnetic seal, replaceable doo locking with vent option, user-fr panel, flexible arrangement of s door shelves with leakage prote control for all operating modes	ight, door with r seals, door iendly control helves, ergonomic	Patented, easy-to-remove freezer compartment Replaceable door seals	
			RML 8551: Manual Energy Sele with electronic gas ignition	ector [MES]	RML 8551:	
			RML 8555 : Automatic Energy S with electronic gas ignition	elector [AES]	Manual Energy Selector [MES] with electronic	
	Test marks		Certified to European Gas Appli 90/396/EEC, e-approved to 200 [Automotive EMC Directive]		gas ignition	
8 ए					RMS 8555: Automatic Energy Selector [AES] with electronic gas ignition	



Dometic RML 8551, door hinge left Dometic RML 8551, door hinge right Dometic RML 8555, door hinge left Dometic RML 8555, door hinge right



Removable, spacious freezer compartment

Absorption refrigerators

Mode

RML 8551, door hinge left RML 8555, door hinge left





XXL-size refrigerator compartment

Dometic 7-Series



From the 7-series: well proven two-door fridges

The two large-capacity models in the successful 7-series provide plenty of room for fresh and deep-frozen food. Separate doors for the fridge and freezer compartments are their "hallmark". For extra convenience, the spacious freezer compartment features a switch-operated frame heater which prevents the door from freezing to the frame. Absolutely reliable and tilt-insensitive up to 5 degrees, 7-series refrigerators provide about 20% more cooling capacity than conventional absorption units. All models with Automatic Energy Selector [AES].

Product highlights at a glance



1. Separate freezer compartment The freezer compartment has a separate door - this avoids unnecessary energy loss as the refrigerator can be opened separately. The switchoperated frame heater prevents the door from freezing to the frame.



refrigerator is not in use.





2. Flexible arrangement of shelves

The improvements are clear to see. Easy-to-remove shelves that can be positioned as needed. Just like at home ...

3. Door locking with vent option

The vent position of the door catch helps provide optimal ventilation when the

4. User-friendly control panel

One knob to select the energy, one push button to activate the frame heating - the control panel combines functionality with aesthetics.

Directly underneath is the easy-to-use door opening.

5. Dimmable LEDs on the control panel

7-series refrigerators are equipped with the AES Automatic Energy Selector and give you the option to dim the LED indicators.

eries absorption refrigera o-door model, 525 mm w	ator for 12 vol	ts, 230 volts and			4.28
	Gross capacity		with freezer compartment incl. freezer compartment	142 litres 25 litres	
and the second s	Energy supply		230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 ml	bar / category lass	*
	Input rating	230 volts 12 volts Gas	190 watts 170 watts 22.5 g/h	C J 3BP	Refrigerator +7°C freezer compartment up to -12°C
Sec. 10	Consumption	230 volts/12 volts Gas	3.2 kWh/24 h 380 g/24 h		
100.00	Cooling capaci	ty	Refrigerator +7°C, freezer comp at ambient temperatures up to [equivalent to climate class SN	32°C	
And the second se	Insulation		Pentane-blown foam [CFC-/H	FC-free]	12/230 volts
Contraction of the local division of the loc	System		Absorption cooling		
1	Material		Cabinet: coated sheet steel Door and panel: plastic		
	Colour		Cabinet: grey, door: grey		U
	Dimensions [W	xHxD]	525 x 1245 x 543 mm		
	Weight		39.5 kg		Gas
	Quality features	5	Door with magnetic seal, varia locking with vent option, user- panel, flexible arrangement of switch-operated frame heater prevents door from freezing to thermostatic control for all ope Automatic Energy Selector [Af electronic gas ignition	friendly control shelves, on the freezer door o the frame, erating modes	Automatic Energy Selector [AES] with electronic gas ignition
	Test marks		Certified to European Gas App 90/396/EEC, e-approved to 20 [Automotive EMC Directive]		Home-like luxury: separate doors for fridge and freezer compartments
1182					Freezer door with switch-operated frame heater to prevent door from
━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━	Product		Model		freezing to the frame
	Dometic RM 760	05.1	RM 7605 L		

Dometic RM 7655 L - with Automatic Energy Selector [AES] 7-series absorption refrigerator for 12 volts, 230 volts and gas Two-door model, 525 mm wide, curved door



Gross capacity		with freezer compartment incl. freezer compartment	150 litres 26 litres	
Energy supply		230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mbar	· / category I _{3 B/P}	
Input rating	230 volts 12 volts Gas	190 watts 170 watts 22.5 g/h		
Consumption	230 volts/12 volts Gas	3.2 kWh/24 h 380 g/24 h		
Cooling capacit	у	Refrigerator +7°C, freezer compar- at ambient temperatures up to 32 [equivalent to climate class SN]		
Dimensions [W:	xHxD]	525 x 1245 x 570 mm		
Weight		40.0 kg		
Further technica	al data	As for Dometic RM 7605 L		

Product Dometic RM 7655 L

RM 7655 L

Energy supply Input rating 230 volts 12 volts Gas Consumption 230 volts/12 volts Gas **Cooling capacity** Insulation System Material Colour Dimensions [WxHxD] Weight Quality features . Test marks Dometic RM 7805 L Dometic RM 7855 L - with Automatic Energy Selector [AES] 7-series absorption refrigerator for 12 volts, 230 volts and gas Two-door model, 525 mm wide, curved door Gross capacity **Energy supply** 230 volts Input rating 12 volts Gas Consumption 230 volts/12 volts Gas **Cooling capacity** Dimensions [WxHxD] Weight Further technical data

Two-door model, 525 mm wide, straight door

Gross capacity

Absorption refrigerators

Dometic RM 7805 L - with Automatic Energy Selector [AES] 7-series absorption refrigerator for 12 volts, 230 volts and gas

with freezer compartment 167 litres incl. freezer compartment 30 litres 230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mbar / category I3 B/P 190 watts 170 watts 22.5 g/h 3.2 kWh/24 h 380 g/24 h

Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C [equivalent to climate class SN]

Pentane-blown foam [CFC-/HFC-free]

Absorption cooling

Cabinet: coated sheet steel Door and panel: plastic

Cabinet: grey, door: grey

525 x 1245 x 599 mm

40.8 kg

Door with magnetic seal, variable door hinge, door locking with vent option, user-friendly control panel, flexible arrangement of shelves, switch-operated frame heater on the freezer door prevents door from freezing to the frame. thermostatic control for all operating modes Automatic Energy Selector [AES] with electronic gas ignition

Certified to European Gas Appliance Directive 90/396/EEC, e-approved to 2006/28/EC [Automotive EMC Directive]

Model

RM 7805 L

with freezer compartment 150 litres incl. freezer compartment 26 litres
230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mbar / category I _{3 в/P}
190 watts 170 watts 22.5 g/h
3.2 kWh/24 h 380 g/24 h
Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C [equivalent to climate class SN]
525 x 1245 x 626 mm
41.3 kg
As for Dometic RM 7805 L



Mode

RM 7855 L

Dometic 4-Series



The 4-series: compact classics

Their reputation is legendary. The tried and tested refrigerators of the 4-series have won innumerable fans among owners of small motorhomes and caravans. They offer astounding value for money and are designed to suit the limited space available in compact leisure vehicles yet are themselves astonishingly roomy. Food storage capacity ranges from 40 litres up to as much as 97 litres and is easily divided into temperature zones - vegetables at the bottom, meat and dairy products at the top. Nearly all models in the 4-series are equipped with a freezer compartment [except RM 4181 M] and are available with an easy-to-use electronic reignition [except RM 4230 L, RM 4210 and RM 4400 L].

- Designed for smaller recreational vehicles
- Low weight, optimised interior and exterior dimensions
- Secure door locking with vent option
- Adjustable shelves.
- additional shelves inside the door
- Available with Piezo or reigniter ignition



User-friendly control panel

ON/OFF switch and turning knob for all functions - the control panel combines functionality with aesthetics.



Adjustable shelves

The refrigerator room can be divided as desired - thanks to the adjustable shelf system. The shelves are easy to clean and feature a retaining bar at the front edge to hold the fridge content in place when the vehicle is in inclined position.



The product name code for the 4-series

Every fridge in this series has a "name" that The last digit refers to the type of ignition. A 0 indicates consists of the letter code RM followed by a Piezo ignition while a 1 stands for reigniter ignition. four-digit number and one or two additional If the four-digit combination is followed by the letter L then letters. These indicate the finish and features of the fridge has an interior light. An M indicates a double lock that particular appliance. top and bottom. The combination LM indicates that both An initial 4 in the four-digit combination indicates that the features are "on board".

refrigerator is part of the 4-series.

If that is followed by a 1 it indicates that the fridge is 401 mm wide. If the second digit is a 2 then the fridge is 486 mm wide while a 4 indicates a width of 525 mm.

Absorption refrigerators

Secure door locking with vent option

The fridge models RM 4211 LM, RM 4281 LM and RM 4401 LM feature a locking system that keeps the door firmly shut tight in every situation. In vent position it provides sufficient ventilation when the refrigerator is not in use.



Dometic RM 4181 M	– with reignite	er ignition		4.28
4-series absorption refriger			dgas	_
Single-door model, 401 mm	wide			
	Gross capacity	,	40 litres	
12 0 0 2	Energy supply		230 volts AC / 50 Hz	
FUNCTION OF			12 volts DC	388
	Input rating	230 volts	Liquefied petroleum gas 30 mbar / category I _{3 B/P} 105 watts	A#A
8-13	inputrating	12 volts	100 watts	Refrigerator +7°C
	Consumption	Gas 230 volts/12 volts	14.7 g/h 2.2 kWh/24 h	
	Cooling capac	Gas	240 g/24 h +7°C at ambient temperatures up to 32°C	
		ity	[equivalent to climate class SN]	STATE OF STATE
	Insulation		Pentane-blown foam [CFC-/HFC-free]	12/230 volts
	System		Absorption cooling	
	Material		Cabinet: coated sheet steel Door: plastic, panel: coated aluminium	
	Colour		Cabinet: grey, door: grey	
	Dimensions [V	/xHxD]	401 x 617 x 451 mm	Gas
	Weight		18.0 kg	
	Quality feature	s	Door with magnetic seal, variable door hinge, double door locking top and bottom with vent option, user-friendly control panel, adjustable shelf, thermostatic control for 230-volt operation, electronic reigniter ignition, 3-stage manual gas	Electronic reigniter ignition
	Test marks		control Certified to European Gas Appliance Directive 90/396/EEC, e-approved to 2006/28/EC [Automotive EMC Directive]	Extremely compact absorption refrigerator
	Product		Model	
	Dometic RM 41	81 M	RM 4181 M	

RM 4181 M

Dometic RM 4210 Dometic RM 4211 LM

Dometic RM 4181 M

Dometic RM 4210 - with Piezo ignition

Single-door models, 486 mm wide

RM 4211 LM

Dometic RM 4211 LM - with reigniter ignition

Gross capacity

Energy supply

Input rating

Consumption

Insulation

System Material

Colour

Weight

Cooling capacity

Dimensions [WxHxD]

Quality features

Test marks

230 volts

230 volts/12 volts

12 volts

Gas

Gas

Absorption refrigerators

4-series absorption refrigerators for 12 volts, 230 volts and gas

with freezer compartment 60 litres incl. freezer compartment 5 litres

- 230 volts AC / 50 Hz
- 12 volts DC Liquefied petroleum gas 30 mbar / category $\rm I_{{}_{3\,B/P}}$ 125 watts
- 120 watts
- 18.3 g/h
- 2.3 kWh/24 h 310 g/24 h
- Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C
- [equivalent to climate class SN]
- Pentane-blown foam [CFC-/HFC-free]
- Absorption cooling
- Cabinet: coated sheet steel Door: plastic, panel: coated aluminium
- Cabinet: grey, door: grey
- 486 x 618 x 474 mm
- 20.7 kg
- Door with magnetic seal, variable door hinge, user-friendly control panel, flexible arrangement of shelves, thermostatic control for 230-volt operation, 3-stage manual gas control
- RM 4210: Gas operation with Piezo ignition, door locking with vent option
- RM 4211 LM: electronic reigniter ignition, interior light, double door locking top and bottom with vent option
- Certified to European Gas Appliance Directive 90/396/EEC, e-approved to 2006/28/EC [Automotive EMC Directive]



4.28

Refrigerator +7°C freezer compartment up to -12°C





Gas

RM 4210: Gas operation with Piezo ignition


RM 4211 LM: Electronic reigniter ignition

Model RM 4210 RM 4211 LM


ies absorption refrig e-door model, 486 n			- -	
	Gross capacity		with freezer compartment 70 litres incl. freezer compartment 5 litres	
	Energy supply		230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mbar / category I _{3 B/P}	
	Input rating	230 volts 12 volts Gas	125 watts 120 watts 18.3 g/h	Refrigerator +7°C freezer compartment up to -12°C
	Consumption	230 volts/12 volts Gas	2.4 kWh/24 h 310 g/24 h	
и 4230 L	Cooling capacit	у	Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C [equivalent to climate class SN]	
	Insulation		Pentane-blown foam [CFC-/HFC-free]	12/230 volts
	System		Absorption cooling	
	Material		Cabinet: coated sheet steel Door: plastic, panel: coated aluminium	
	Colour		Cabinet: grey, door: grey	
	Dimensions [W	xHxD]	486 x 821 x 474 mm	
	Weight		22.2 kg	Gas
486 95 340	Quality features	5	Interior light, door with magnetic seal, variable door hinge, door locking with vent option, flexible arrangement of shelves, thermostatic control for 230-volt operation, gas operation with Piezo ignition, 3-stage manual gas control	Gas operation with Piezo ignition
	Test marks		Certified to European Gas Appliance Directive 90/396/EEC, e-approved to 2006/28/EC [Automotive EMC Directive]	
89 K 82 K 215				
57	Product		Ref. No.	
I	Dometic RM 423	60 L	RM 4230 L	



RM 4281 LM



	Gross capacity		with freezer compartment 80 litres incl. freezer compartment 5 litres		
	Energy supply		230 volts AC / 50 Hz 12 volts DC Liquefied petroleum gas 30 mbar / category I _{3 в/P}	*	
	Input rating	230 volts 12 volts Gas	125 watts 120 watts 18.3 g/h	Refrigerator +7°C freezer compartment up to -12°C	
	Consumption	230 volts/12 volts Gas	2.5 kWh/24 h 270 g/24 h		
	Cooling capacit	ty	Refrigerator +7°C, freezer compartment up to -12°C at ambient temperatures up to 32°C [equivalent to climate class SN]		
	Dimensions [W	xHxD]	486 x 821 x 474 mm	12/230 volts	
	Weight		23.0 kg	-	
→ 39	Quality features		Interior light, door with magnetic seal, variable door hinge, double door locking top and bottom with vent option, flexible arrangement of shelves, thermostatic control for 230-volt and gas peration, electronic reigniter ignition		
	Further technic	al data	As for Dometic RM 4230 L	Gas	
				Electronic reigniter ignition	
	Product		Model		
	Dometic RM 428	31 LM	RM 4281 LM		



Dometic RM 4400 L - with Piezo ignition

Single-door models, 525 mm wide

Dometic RM 4401 LM - with reigniter ignition

Gross capacity

Energy supply

Input rating

Consumption

230 volts

230 volts/12 volts

12 volts

Gas

Gas

Absorption refrigerators

4-series absorption refrigerators for 12 volts, 230 volts and gas

with freezer compartment 97 litres including freezer compartment 10.5 litres

- 230 volts AC / 50 Hz
- 12 volts DC
- Liquefied petroleum gas 30 mbar / category $\rm I_{{}_{3\,B/P}}$ 125 watts
- 120 watts
- 18.3 g/h
- 2.6 kWh/24 h 270 g/24 h
- Refrigerator +7°C, freezer compartment up to -12°C
- at ambient temperatures up to 32°C [equivalent to climate class SN]
- Pentane-blown foam [CFC-/HFC-free]
- Absorption cooling
- Cabinet: coated sheet steel Door: plastic, panel: coated aluminium
- Cabinet: grey, door: grey
- 525 x 805,5 x 537 mm
- RM 4400 L: 29.0 kg, RM 4401 LM: 29.0 kg
- Interior light, door with magnetic seal, variable door hinge, flexible arrangement of shelves, thermostatic control for 230-volt and gas operation
- RM 4400 L: gas operation with Piezo ignition, door locking with vent option
- RM 4401 LM: electronic reigniter ignition, double door locking top and bottom with vent option Certified to European Gas Appliance Directive 90/396/EEC, e-approved to 2006/28/EC [Automotive EMC Directive]



4.28

Refrigerator +7°C freezer compartment up to -12°C





Gas

RM 4400 L: gas operation with Piezo ignition

RM 4401 LM: electronic reigniter ignition


Full-width freezer compartment


Model RM 4400 L RM 4401 LM

Perfect ventilation for perfect performance

Sufficient ventilation prevents heat build-up behind the refrigerator. This ensures you will get the maximum performance.

Other advantages of the purpose-designed ventilation systems are: reduced energy consumption, and easy access for service and maintenance, e.g. for cleaning the burner **without** having to remove the refrigerator. The ventilation grills are attached on the outside of the vehicle: the lower grill guides cool air to the rear of the refrigerator, the upper grill allows heated air to escape. Both ventilation grills feature a comfortable sliding lid and a bracket for the condensation hose.





models: Upper ventilation grill LS100 and lower ventilation grill LS 200. Both are an upper or lower ventilation grill. It is refrigerator we recommend you use attached to the outside of the vehicle.



attached to the outside of the vehicle.

Ventilation grills for single-door Ventilation grill for two-door Roof ventilation: When your vehicle's models: The LS 300 can be used as awning is on the same side as the the R 500 roof ventilation, which can be combined with other Dometic ventilations systems.



Winter set for LS 300 for two-door models: The polyurethane foamed ventilation grill significantly enhances the refrigerator's insulation rating. Equipped and electricity mode even at temperatures as low as -30°C. For temperatures above 5°C we recommend you use a standard cover.



Ventilator set: Speeds up the airflow, cools down the condenser and ensures optimal ventilation of your absorption refrigerator. Very easy to install and highly recommended when travelling in high ambient temperatures and intense sun exposure.

with the winter cover, the absorption unit The Dometic ventilator is thermostat controlled and operates on 12 volts. It is the only reaches its maximum performance in gas product of this kind to comply with e1 regulations.

Comfort accessories and spares for 8-/7-/4-series



No cracked eggs, no mess in the fridge! A breath of fresh air! The activated Ignition without delay: battery igniter 8-series refrigerators.



Up to six eggs can be safely stored in the **carbon filter** by Dometic eliminates for retrofitting on all Piezo-fridges with egg shelf. Simply place on a grid shelf or odours in refrigerators, cupboards or plastic dashboard holders manufactured in the door rack. Suitable for all 4-, 7- and storage compartments. Effective for about after the 1st of January 1998. Simply press one year, it is easily replaced and disposed and hold the button until the gas has of in an environmently friendly way with the been ignited. Trouble-free installation, quick domestic waste.

Ventilation accessories for 8-/7-/4-series Ventilation grills / winter set / roof ventilation / ventilator set

Product



Vetilation grills LS 100, top, white LS 100, top, beige LS 200, bottom, white LS 200, bottom, beige LS 300, white, [with winter cover] LS 300, white, [without winter cover]

Roof ventilation R 500, white



Ventilator Ventilator set



Winter cover set WA 120/130, top/bottom, for LS100/LS200, white WA 120/130, top/bottom, for LS100/LS200, beige EWS 300, winter set for LS 300, white

Comfort accessories and spares for 8-/7-/4 Egg shelf / activated carbon filter / battery igniter



Accessories for absorption refrigerators



battery exchange.

rt	4.28
Ref. No.	
9105900012 9105900011 9105900014 9105900013 9105900015 9105900016	Components for optimal ventilation
9105900020	
9105900007	
9105900018 9105900019 9105900017	
4-series	4.28
Ref. No.	
9105900009	
9105900008	
9105900010	
rement	84-85